

auto electrical parts

Technical Information Sheet

Part No. 0-932-range

Single core PVC thin wall auto cable to ISO6722/4.

Additional Information

0-932-01	black	0-932-37	brown/white
0-932-02	blue	0-932-38	brown/yellow
0-932-03	brown	0-932-40	light green
0-932-04	green	0-932-41	green/black
0-932-05	red	0-932-42	green/blue
0-932-06	purple	0-932-43	green/brown
0-932-07	white	0-932-45	green/red
0-932-08	yellow	0-932-46	green/purple
0-932-09	grey	0-932-47	green/white
0-932-10	orange	0-932-48	green/yellow
0-932-11	pink	0-932-51	red/black
0-932-12	black/blue	0-932-54	red/green
0-932-14	black/green	0-932-57	red/white
0-932-15	black/red	0-932-58	red/yellow
0-932-18	black/yellow	0-932-61	purple/black
0-932-21	blue/black	0-932-67	purple/white
0-932-23	blue/brown	0-932-71	white/black
0-932-24	blue/green	0-932-72	white/blue
0-932-25	blue/red	0-932-73	white/brown
0-932-27	blue/white	0-932-74	white/green
0-932-28	blue/yellow	0-932-75	white/red
0-932-31	brown/black	0-932-81	yellow/black
0-932-34	brown/green	0-932-82	yellow/blue
0-932-35	brown/red	0-932-87	yellow/white



Technical Drawing (not to scale)



Specification

Type	Single core thin wall cable
Wire	32/0.20mm copper
Cross section	1.00mm ²
Current rating	16.5 amp
Voltage	60 volt dc maximum
Resistance	18.5mΩ/m @ 20°C
Insulation	Hard grade PVC to BS6746 Type 5
Overall diameter	2.3mm
Temperature	-40° to 105°C (120°C intermittant)

The information contained in this document is correct to the best of our knowledge at the time of printing. However, specifications may change at any time without notice.

Gordon Equipments Limited

Durite Works
Valley Road
Dovercourt
Essex CO12 4RX
England



Tel: +44 (0)1255 555200
Fax: +44 (0)1255 555222
E-mail: sales@durite.co.uk
Web: www.durite.co.uk

Registered in England at address shown No. 373113
The words 'Gordon', 'Durite', 'Nolten' and 'Acfil' are registered trade marks